

Patent Application of

Charles A. Lowry

for

LIQUID PURIFYING DEVICE

5

BACKGROUND OF THE INVENTION

1. FIELD OF THE INVENTION.

The present invention and Patent Office Disclosure 472958 relates to a device for purifying liquids, and particularly relates to such a liquid purifying device utilizing the process of distillation/evaporation of volatile contaminants contained within a liquid to separate and remove such volatile contaminants from the contaminated liquid, and more particularly relates to such a device that utilizes a distillation/evaporation chamber which is mounted in place of or complementing the standard factory liquid filtering system.

15 2. DESCRIPTION OF THE PRIOR ART.

There presently exist a number of distillation-type liquid separation and reclamation devices for distillation/evaporation and removal of volatile contaminants from contaminated liquid. Most of these units are utilize what is called the thin-film evaporation process, wherein the oil is passed over a heated flat horizontal surface (evaporation plate), the theory being that the heat will cause the oil to flow to such a "thin

20

film" on the flat horizontal surface that volatile contaminants having a boiling point lower than that of the temperature of the evaporation plate will be evaporated, followed by a collection of the "purified" oil following contaminant evaporation. In addition, most of these thin-film evaporation-type distillation units incorporate a separate heating element
25 (generally electric) for maintaining the evaporation plate at the desired temperature. Typical of these units are shown in U.S. Patent Nos. 1,718,800, 2,472,717, and 4,006,084.

One of the problems with these prior art thin-film is that an electric heating element in the general vicinity of volatile contaminants and engine fuel creates a
30 potentially explosive environment. Another problem with prior art thin-film is that they are complicated and expensive to manufacture and service.

Additionally, most of these units require external mounting equipment and a convenient location for the placement of these devices. Oil distillation/evaporation units of this type are shown in U.S. Pat. Nos. 1,718,800, 2,472,717, 2,839,196, 3,198,104,
35 3,756,412, 4,006,084, 4,115,201, 4,189,351, 4,146,475, 4,289,583, 4,443,334, 4,349,438, 4,354,946, 4,369,110, 4,717,474, 4,830,745, 4,943,352, 5,242,034, 5,322,596; 5,630,912, 5,630,912, and applicants own U.S. Patents Nos. 5,824,211 and 5,776,315. All these patents disclose liquid purifying device designs which are mounted remotely from the source of the liquid. None of the prior art utilizes an existing filtration system to effect a
40 simple and effective liquid supply and mounting system for the liquid purifying device such as the system illustrated in this patent application.

There remains a need for an efficient evaporation apparatus that is small enough for use in a wide variety of applications while not being limited to the conventional means of liquid supply and liquid purifying device placement and mounting. However, at
45 the time the present liquid purifying device was made, it was not obvious to those of ordinary skill in the art how those needs could be fulfilled, in view of the prior art as a whole.

OBJECT OF THE INVENTION

50 It is therefore an object of the present invention to provide a device for removing volatile contaminants from liquid that utilizes heat from the liquid to effect vaporization of the contaminants, rather than a separate heating element.

It is further object of the present invention to provide such a device that is small and compact, and conveniently fastens to existing liquid filter mounts.

55

SUMMARY OF THE INVENTION

The liquid purifying device (10) of the present invention is utilized for separating and removing volatile contaminants from liquids. In one embodiment, the device incorporates a self-contained particle filter (32) for filtering particles from the
60 contaminated liquid. The liquid purifying device (10) itself comprises a distillation/evaporation chamber positioned essentially between the liquid source and the particle filter, and receives contaminated liquid that has been filtered by the filter media

(20). The filtered contaminated liquid is passed through the liquid metering orifice (26), whereupon the oil enters the distillation/evaporation chamber (22). Upon entering the
65 distillation/evaporation chamber (22) the metered liquid spreads in a thin film, thereby effecting the distillation/evaporation process.

Heat for distillation/evaporation of the volatile contaminants from the liquid acting directly within the distillation/evaporation chamber (22) is provided by the heated liquid itself, without the necessity of a separate heating element to maintain the
70 vaporization temperature of the distillation/evaporation chamber.

This distillation/evaporation process is based on the well known principles of the thin-film evaporation process, wherein a liquid is spread into a thin film and heated, thus allowing trapped volatile elements such as water, gasoline, trapped gases, etcetera, within the liquid to be evaporated and vented outside the liquid purifying device.

75 This liquid purifying device is typically used in a full-flow filter capacity with an internal combustion engine, whereby a small amount of contaminated engine oil is tapped from the normal oil flow through the filter and processed through the liquid purifying device, whereupon the volatile contaminants are vaporized, separated, and removed from the oil. The processed lubricating oil is then returned to the engine oil pan through
80 purified liquid exit (24). The liquid to be purified communicates to the filter through a plurality of liquid filter communicating conduits (12) such that certain conduits allow liquid to flow to the filter and certain other conduits allow liquid to return to the source with little or no impedance in overall liquid flow. This liquid purifying device effectively

utilizes the existing liquid filter mounting system to facilitate its own mounting and
85 provide a convenient source of liquid.

In other application, the particle filter may or may not be used. Rather, contaminated liquid-hydraulic liquid, machining oil, cooking oil, heating/cooling liquid, etc. - with or without pre-heating - may be pumped directly into the distillation/evaporation chamber for evaporation, distillation, and removal of volatile
90 contaminants therefrom, the processed liquid then being returned to the mechanism in which it is used.

A first feature of this liquid purifying device is the improved utilization of space by the use of the existing liquid filter mounting system. This utilization brings the
95 benefits of a compact installation with a direct liquid source and convenient placement with minimum difficulty of installation and maintenance. Another benefit of this design is the efficient use of the heat inherent to most liquid sources to heat the evaporation chamber evenly and effectively without the need of any additional heat source, which eliminates the need for potentially dangerous heating elements while improving
100 efficiency and reducing manufacturing costs.

Thus it is understood that a primary object of this liquid purifying device is to advance the art of liquid purifying by providing a device with is easily and conveniently mounted, simple to maintained, safer and more reliable operation, and is useful in a much greater range of applications.

105

These and other important objects, features and advantages of this liquid purifying device will become apparent as this description proceeds.

110 This liquid purifying device accordingly comprises the features of construction, combination of elements and arrangement of parts that will be exemplified in the construction hereinafter set forth, and the scope of this liquid purifying device will be indicated in the claims.

BRIEF DESCRIPTION OF THE DRAWINGS

115

Other objects of this liquid purifying device will appear in the following description and appended claims, reference being made to FIGS. 1-20 forming a part of the specification wherein like reference characters designate corresponding parts.

120 FIG. 1 is a vertical sectional view of the liquid purifying device of the present invention including the particulate filter.

FIG. 2 is a top plan view of a first embodiment of the liquid purifying device.

FIG. 3 is a bottom plan view of a first embodiment of the liquid purifying device.

FIG. 4 is a horizontal sectional view of a first embodiment of the liquid purifying device.

125

said view taken in the direction of arrows 1--1 in FIG 1.

FIG. 5 is a vertical sectional view of a first alternative design of the liquid purifying device.

FIG. 6 is a top plan view of a first alternative design of the liquid purifying device.

FIG. 7 is a bottom plan view of a first alternative design of the liquid purifying device.

130 FIG. 8 is a horizontal sectional view of a first alternative design of the liquid purifying device, said view taken in the direction of arrows 2--2 in FIG 5.

FIG. 9 is a vertical sectional view of a second alternative design of the liquid purifying device.

135 FIG. 10 is a vertical sectional view of a third alternative design of the liquid purifying device.

FIG. 11 is a vertical sectional view of a fourth alternative design of the liquid purifying device.

FIG. 12 is a top plan view of a forth embodiment of the liquid purifying device.

FIG. 13 is a bottom plan view of a forth embodiment of the liquid purifying device.

140 FIG. 14 is a horizontal sectional view of a forth embodiment of the liquid purifying device, said view taken in the direction of arrows 3--3 in FIG 11.

FIG. 15 is a vertical sectional view of a fifth alternative design of the liquid purifying device.

145 FIG. 16 is a vertical sectional view of a sixth alternative design of the liquid purifying device.

FIG. 17 is a top plan view of a sixth embodiment of the liquid purifying device.

FIG. 18 is a bottom plan view of a sixth embodiment of the liquid purifying device.

FIG. 19 is a horizontal sectional view of a sixth embodiment of the liquid purifying device, said view being taken along line 4--4 in FIG 16.

150 FIG. 20 is a vertical sectional view of a seventh alternative design of the liquid purifying device.

LIST OF REFERENCE NUMERALS

- | | | |
|-----|----|---|
| 155 | 10 | Liquid purifying device. |
| | 12 | Liquid filter communicating conduits. |
| | 14 | Liquid refiner to liquid source attachment means. |
| | 16 | Liquid seals. |
| | 18 | Distillation/evaporation chamber lid. |
| 160 | 20 | Vapor vent. |
| | 22 | Distillation/evaporation chamber. |
| | 24 | Refined liquid exit. |
| | 26 | Liquid metering orifice. |
| | 28 | Liquid diverting obstruction. |
| 165 | 32 | Liquid filter. |
| | 34 | Liquid source. |
| | 36 | Liquid filter element. |

38 Distillation/evaporation chamber lid attachment means.

40 Filter to liquid purifying device attachment means.

170

DESCRIPTION OF SPECIFIC EMBODIMENTS

The liquid purifying device of the present invention has application in many environments. For example, the device may be used to supplement factory filter systems in internal combustion engines in both mobile and stationary applications. It is also contemplated that the present liquid purifying device will have application in hydraulic systems, and in industrial applications wherever hydraulic liquid (oil), cutting (machining) oil, drilling liquid, cooking oil, cleaning liquids, cooling/heating liquids, etc. are used. For purposes of description and explanation of the concept of the liquid purifying device, however, and without limiting the concept or application of the invention, the liquid purifying device will be described in an application of an oil-lubricated internal combustion engine.

Turning now to the drawings, and initially to Fig. 1, the liquid purifying device is shown generally illustrated by the numeral 10. The device includes a combination liquid purifying device to liquid source attachment means (14), filter to liquid purifying device attachment means (40), liquid communication conduits (12), and liquid filter (32). Oil from the engine flows through the liquid purifying device through the liquid communication conduits(s) (12) unimpeded to the liquid filter (32), which oil passes

through the liquid filter (32) in the customary manner and returns to the engine through
190 additional liquid communication conduit(s) (12) allowing the liquid purifying device to
be mounted in-between the engine and the conventional oil filter while retaining the
function of the conventional filter with the added capabilities of volatile contaminate
removal.

The liquid refining device 10 includes a contaminated oil metering orifice (26) for
195 conducting oil under pressure from the engine oil pump (not shown) to the
distillation/evaporation chamber while simultaneously moderating the oil delivery rate to
between 0.5 and 20 gallons per hour, although other flow rates are within the scope of
this liquid purifying device. The styles of metering orifice and oil filters used in this oil
refining device are well known and in common use.

200 The distillation/evaporation chamber is located in-between the engine and filter
for a number of reasons: (1) simplicity; (2) efficient use of space; (3) to maintain the oil
at the proper temperature for contaminant evaporation; (4) minimization of oil piping and
connections. In a preferred embodiment of the present invention, a three micron
particulate filter is used for the filter media in order to optimize the filtration.

205 The specific apparatus for separating and removing the volatile contaminates from
the oil is the distillation/evaporation chamber (22). The distillation/evaporation is simply
a chamber of the proper shape and dimensions such as to promote the spreading of the oil
into a thin film, and including an oil metering orifice (26), a vapor vent (20), and a
purified oil exit (24). The distillation/evaporation chamber is enclosed by the

210 distillation/evaporation lid (18), which is secured by the distillation/evaporation lid attachment means (38). In the preferred embodiment as observed in Fig. 1, the distillation/evaporation chamber (22), oil metering orifice (26), purified oil exit (24), and vapor vent (20) may all be incorporated into a single housing. The simplicity of this design is one of its greatest strengths.

215 As can be seen by the accompanying figures, the proper shape and dimensions of the distillation/evaporation chamber may vary widely according to the desired flow rate and liquid to be purified. Fig. 1 illustrates one such shape and dimensions wherein the shape of the distillation/evaporation chamber is an annular ring with a height roughly equivalent to twice the width of the chamber. Included in most embodiments of the
220 liquid purifying device and specifically in Fig. 4, there can be seen a liquid diverting obstruction (28) which redirects the oil flow along the length of the distillation/evaporation chamber to the purified oil exit.

Referring again to Fig. 1, it can be seen that purified liquid exit (24) communicates the purified out from the distillation/evaporation chamber (22) to a
225 location outside the chamber (which in the case of installation on an internal combustion engine, the oil would be communicated to an oil return line which returns the oil to the engine). Additionally, it can also be seen that vapor vent (20) communicates vaporized contaminants from within the distillation/evaporation chamber (22) to a location outside the chamber.

230

OPERATION

In the first preferred embodiment as illustrated by Figs. 1 - 4, the oil to be processed passes unimpeded through the body of the liquid refining device to the filter through the liquid filter communication conduits (12), flows through liquid filter (32) in the customary manner, and most of the oil returns to the engine by way of the additional liquid filter communication conduit (12) located centrally to the filter.

Contaminated oil to be purified enters the distillation/evaporation chamber (22) at the liquid metering orifice (24). This contaminated oil is under pressure, and can come from the oil source (as shown in Fig. 20) or the conventional oil filter outlet.

The oil, upon entering the distillation/evaporation chamber (22) experiences a sudden pressure drops considerably (to ambient or atmospheric pressure), due of course, to the metering orifice. The sudden drop of pressure facilitates evaporation of volatile contaminants that have been emulsified in the oil during its lubrication function.

The oil, as it flows within the distillation/evaporation chamber (22) is controlled in its direction of flow by the liquid diverting obstruction (28) so as to maximize the length of travel of the oil within the distillation/evaporation chamber and thusly maximize the efficiency of volatile removal. Also, as the oil flows through the distillation/evaporation chamber (22), it flows in a thin-film, which effects the thin-film evaporation of the volatile contaminants from the oil. This thin-film evaporation process may be greatly enhanced by the heat contained within the oil itself as the engine reaches operating temperature.

Those skilled in the art will appreciate that the distillation/evaporation chamber need not be perfectly vertical while oil is being processed therethrough. This is because as the oil flows through the distillation/evaporation chamber, the natural vibrations inherent in most liquid sources, and in particular internal combustion engines, inputs physical forces into the flow of the oil resulting in a churning and lapping action of the oil within the distillation/evaporation chamber (22) which evenly coats the interior of the chamber with a thin film of oil, thereby causing increased efficiency in evaporation of the volatile contaminants from within the oil.

Once flowing, this oil flow will remain continuous and uninterrupted throughout the distillation/evaporation chamber, whereupon the oil exits the distillation/evaporation chamber by way of purified liquid exit (24) to be returned to the engine.

As can be appreciated, as these various volatile contaminants vaporize and are distilled from the initially contaminated oil, the accumulation of vapor requires a means of exhaust. Because of the fact that the distillation/evaporation chamber forms essentially a closed system, the pressure within the closed system, and therefore within the liquid channel (38) remains essentially constant. Therefore, as the various contaminants vaporize and expand, the vapor is forced through the vapor vent (20). In addition, in certain mobile and industrial applications, a negative pressure (a separate vacuum) can be used to withdraw the released vaporized contaminants from the evaporation chamber.

FIRST ALTERNATIVE EMBODIMENT

Figs. 5 - 8 illustrates a first alternative embodiment of the liquid purifying device.

275 The first alternative embodiment of Fig. 5 illustrates the use of an alternate means of attachment of both the liquid purifying device to the source (engine) and of the filter to the device by the use of an attachment means (40) which extents completely through the filter housing through the liquid purifying device to the liquid source. Additionally, the full flow of the oil to be purified is directed through the liquid purifying device so that all oil is purified before being returned to use.

280

SECOND ALTERNATIVE EMBODIMENT

The second alternative embodiment of Fig. 9 illustrates the use of an extended distillation/evaporation chamber, which extension extends longitudinally to the filter and surrounds the filter. Within this extension is a spirally extending distillation/evaporation
285 chamber which effects a longer evaporation path for increased volatile removal efficiency. Additionally, the full flow of the oil to be purified is directed through the liquid purifying device so that all oil is purified before being returned to use.

THIRD ALTERNATIVE EMBODIMENT

290 The third alternative embodiment of Fig. 10 illustrates the use of an extended distillation/evaporation chamber, which extension extends longitudinally to the filter and surrounds the filter. Within this extension is a cascading and downwardly projecting array of fins which effects a longer evaporation path for increased volatile removal

efficiency. Additionally, the full flow of the oil to be purified is directed through the
295 liquid purifying device so that all oil is purified before being returned to use.

FORTH ALTERNATIVE EMBODIMENT

Figs. 11 - 14 illustrates a second alternative embodiment of the liquid purifying device. The forth alternative embodiment of Fig. 11 illustrates the use of a liquid purifying device to source attachment means (14) which comprises a bolt which itself
300 comprises a liquid flow conduit (14) for allowing the device to be offset-mounted. This means of mounting allows the device to be installed in otherwise space restricted areas. Additionally, the distillation/evaporation chamber is constructed in a non-annular fashion, but instead is grouped to one general location within the liquid purifying device, while the liquid conduits are themselves also grouped within the liquid purifying device as
305 shown.

FIFTH ALTERNATIVE EMBODIMENT

The fifth alternative embodiment of Fig. 15 illustrates the use of a horizontally mounted liquid purifying device which incorporates the liquid metering orifice (26) and
310 the vapor vent (20) in the uppermost location, while the purified liquid exit (24) is located in the lowermost location. No liquid diverting obstruction (28) is used with this embodiment so as to allow the oil to flow evenly and uniformly down all interior surfaces of this horizontally mounted embodiment.

315

SIXTH ALTERNATIVE EMBODIMENT

Figs. 16 - 19 illustrates a second alternative embodiment of the liquid purifying device. The sixth alternative embodiment of Fig. 16 illustrates the use of distillation/evaporation lid (16) which is engaged as part of the liquid purifying device by means of a press fit, thereby eliminating the need for additional lid attachment means.

320 Additionally, the distillation/evaporation chamber is constructed so as to facilitate installation by incorporating a plurality of vapor vents (20) and purified liquid exits (24). This allows the user to install the device without concern whether the vapor vent or liquid exit will be located in the proper orientation. The user ability to install the device and then select the appropriate vapor vent and liquid exit locations for proper operation will
325 greatly enhance the installation procedure.

SEVENTH ALTERNATIVE EMBODIMENT

The seventh alternative embodiment of Fig. 20 illustrates the construction of a liquid refining device which does not use a filter.

330

This liquid purifying device is clearly new and useful. Moreover, it was not obvious to those of ordinary skill in the art at the time it was made, in view of the prior art considered as a whole as required by law.

335

It will thus be seen that the objects set forth above, and those made apparent from the foregoing description, are efficiently attained and since certain changes may be made

in the above construction without departing from the scope of this liquid purifying device, it is intended that all matters contained in the foregoing construction or shown in the accompanying drawings shall be interpreted as illustrative and not in a limiting sense.

340

It is also to be understood that the following claims are intended to cover all of the generic and specific features of this liquid purifying device herein described, and all statements of the scope of this liquid purifying device which, as a matter of language, might be said to fall therebetween.